

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/114440 A2

(51) International Patent Classification⁷: **H01M 4/04**

(21) International Application Number:
PCT/JP2004/007864

(22) International Filing Date: 31 May 2004 (31.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-174135 18 June 2003 (18.06.2003) JP

(71) Applicant (for all designated States except US): NISSAN
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-
gawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WATANABE, Ky-
oichi [JP/JP]. HORIE, Hideaki [JP/JP]. SHIMAMURA,
Osamu [JP/JP]. SAITO, Takamitsu [JP/JP].

(74) Agents: MIYOSHI, Hidekazu et al.; 9th Floor, Tora-
nomon Daiichi Building, 2-3, Toranomom 1-chome, Mi-
nato-ku, Tokyo 1050001 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTRODE, BATTERY, AND METHOD OF MANUFACTURING THE SAME



(57) Abstract: An electrode (100) of the present invention contains a collector (104) and an electrode layer (102) which is disposed on the collector (104) and contains an active material. In the electrode (100), an average thickness (h) of the collector (104) and the electrode layer (102) ranges from 5 to 300 (nm), and a maximum thickness (h) of the collector (104) and the electrode layer (102) is not more than 105% of a minimum thickness (h) of the collector (104) and the electrode layer (102). The electrode (100) is very thin and the uniformity of the electrode layer (102) is high. Therefore, the heat dissipation characteristics of the battery (300) are uniform, the local degradation is hardly generated in the battery (300), and the crack and the rupture are also hardly generated in the battery (300).

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/114440 A3

(51) International Patent Classification⁷: H01M 4/04, 4/88

(21) International Application Number:
PCT/JP2004/007864

(22) International Filing Date: 31 May 2004 (31.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-174135 18 June 2003 (18.06.2003) JP

(71) Applicant (for all designated States except US): NISSAN
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-
gawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WATANABE, Ky-
oichi [JP/JP]. HORIE, Hideaki [JP/JP]. SHIMAMURA,
Osamu [JP/JP]. SAITO, Takamitsu [JP/JP].

(74) Agents: MIYOSHI, Hidekazu et al.; 9th Floor, Tora-
nomon Daiichi Building, 2-3, Toranomom 1-chome, Mi-
nato-ku, Tokyo 1050001 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report

(88) Date of publication of the international search report:
3 March 2005

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTRODE, BATTERY, AND METHOD OF MANUFACTURING THE SAME



(57) Abstract: An electrode (100) of the present invention contains a collector (104) and an electrode layer (102) which is disposed on the collector (104) and contains an active material. In the electrode (100), an average thickness (h) of the collector (104) and the electrode layer (102) ranges from 5 to 300 (nm), and a maximum thickness (h) of the collector (104) and the electrode layer (102) is not more than 105% of a minimum thickness (h) of the collector (104) and the electrode layer (102). The electrode (100) is very thin and the uniformity of the electrode layer (102) is high. Therefore, the heat dissipation characteristics of the battery (300) are uniform, the local degradation is hardly generated in the battery (300), and the crack and the rupture are also hardly generated in the battery (300).